

Pile Driving Analyzer® Model 8G

System for dynamic load testing and pile driving monitoring




Bearing capacity of all types of deep foundations

The **Pile Driving Analyzer** (PDA) system acquires data from **accelerometers** and **strain transducers** attached to a pile or shaft so that High Strain Dynamic Tests (ASTM D4945) may be performed. The tests require the impact of a pile driving hammer or, if that is not available, of a suitable drop weight.

High Strain Dynamic Load Test with the PDA-8G

The **PDA-8G assesses bearing capacity and structural integrity**. Preliminary field results are further analyzed with the CAPWAP® software, for results that correlate extremely well with static load tests. High Strain Dynamic Load Tests may be performed on drilled shafts, continuous flight auger, cast-in-situ or driven piles on a restrike. The PDA-8G is particularly attractive for drilled shaft testing, offering the option of conducting the test with four or more wireless strain transducers.



The PDA-8G is sleek, light and ergonomic. Its large screen responds to gesture controls like swiping and pinch-to zoom.



PDA-8G in the field

SiteLink® (Remote Testing*)

- The engineer performs Pile Driving Monitoring or Dynamic Load Tests from any office
- Real time field to office data transmission via Internet
- All field measured signals and results on a computer running PDA-S software
- Simple field setup may be performed by a technician

The PDA-8G may also be used by a field engineer on location, displaying results, measured signals and all variables of interest on its screen.

**U.S. Patent No. US 6,301,551 B1*

Pile Driving Monitoring

Pile Driving Monitoring helps establish the Driving Criterion and contributes to safe and economical production pile installation. **The PDA-8G reveals the capacity of driven piles at the time of testing (by Case Method and iCAP®), driving hammer performance, driving stresses, and pile integrity.** The fast data transmission of the PDA-8G allows testing during driving with hammers with very fast operation without loss of data.

The PDA may meet Rapid Load Test standards (ASTM D7383) when a ram of sufficient mass is used.

Wireless Mode

- No cables from the accelerometers and strain transducers to the PDA.
- Fast signal transmission of up to 100 m (330 ft) through WiFi

The PDA-8G may also be used with cabled (traditional) accelerometers and strain transducers.



Receiving test data with SiteLink.


Quality Assurance for Deep Foundations

Four or Eight Universal Data Channels

Most High Strain Dynamic Tests require only 2 strain transducers and 2 accelerometers installed near the top of the foundation. These 2 pairs of sensors are sufficient to obtain the force and velocity records needed for the PDA calculations, thus making four channels of data acquisition adequate for the test.

Eight channels of data acquisition - 4 strain transducers and 4 accelerometers - are recommended for dynamic tests of augered cast-in-place / continuous flight auger piles, drilled shafts and spiral-welded pipes. Eight channels are also essential for dynamic measurements to be made simultaneously on follower and pile, and when a pair of accelerometers and strain transducers is installed at a second location along the length of the foundation (for example by embedding sensors near the toe of a concrete pile).

If a drop weight is to be instrumented to measure force by Newton's Law, then eight channels are also required. **The 8 channels of data acquisition of the PDA model 8G are universal; any combination of accelerometers and strain transducers may be used; all channels are compatible with Smart Sensors (no need to input sensor calibration).**



clockwise from top right: Wireless Transmitter, Accelerometer and Strain Transducer

Engineers around the world have been using the PDA for more than four decades. High Strain Dynamic Tests performed with the PILE DRIVING ANALYZER are standardized by ASTM 4945 and are recognized by, among others, National Codes of Australia, Brazil, Canada, China, Egypt, Qatar, United Kingdom and Eurocode 7; International Building Code (USA); American Association of State Highway Officials, US Federal Highway Administration and most US Departments of Transportation; regional, provincial or municipal governments in Argentina, Mexico and the Philippines; the American Society of Civil Engineers, Deep Foundations Institute and Pile Driving Contractors Association.

Please contact Pile Dynamics for information on compliance with standards from other countries.




Selected PDA-8G Features: 320 X 250 X 68 mm, 5 kg, 4 hour internal battery, Microsoft Windows® 7 Operating System, 60 GB SSD internal drive, Ethernet port, 4 USB ports. For complete current specifications visit www.pile.com/specifications.

Software:

PDA software suite: PDA-S iCAP®, PDILOT, PDI-Curves

- **PDA-S** offers a more intuitive interface than former PDA programs, and runs both in the PDA-8G and in an office computer during post processing, offering both touchscreen and desktop functionality and simplifying the software learning process. In addition to soil resistance at the time of the test, PDA-S outputs a vast array of other variables, customized by the user for each application. PDA-S also issues warnings and alerts during data input and acquisition. It outputs fully customized graphs, with up to three graphs appearing on the screen in real time.
- **iCAP** calculates capacity at the time of testing through a signal matching procedure performed during Pile Driving Monitoring. Because it is based on CAPWAP® logic, it is a step beyond capacity determined by the Case Method. With no user interaction, iCAP extracts the soil behavior from dynamic measurements, computes capacity at the time of test, and produces a simulated static load test graph in real time. The PDA-8G offers one touch iCAP results in the field.
- **PDILOT2** generates tables and plots of any PDA quantity PDA versus blow number, length, elevation or any other quantity. It provides the statistical summary output required by ASTM D4945 and is fully customizable.
- **PDI-CURVES** combines plots of Force-Velocity versus time (required by ASTM D4945), and of other quantities from multiple PDA-S files in one single document.



PDA-S software

CAPWAP uses force and velocity records measured by the PDA sensors to, by signal matching, determine resistance distribution and dynamic soil response and simulate a static load test. Hundreds of comparisons demonstrate the excellent correlation of CAPWAP analysis with static load testing results. CAPWAP analysis of PDA data is standard practice for Dynamic Load Testing.

GRLWEAP is a wave equation analysis program that simulates pile driving. It can be used to select the hammer for pile driving or to evaluate the suitability of a drop weight system for the Dynamic Load Test of a drilled shaft.



Pile Dynamics, Inc.

30725 Aurora Road
Cleveland, OH 44139 USA

Printed on recycled paper.
© 2014, Pile Dynamics, Inc.
Specifications subject to change without notice.



+1-216-831-6131 info@pile.com www.pile.com